VARi IT 501-

THE VARIABLE PRO FOR THE INDUSTRIAL AND NETWORK ENVIRONMENT

VARi IT 501 - MAXIMUM FLEXIBILITY

- Wall mounting ▪ Floor mounting with adjustable feet or plinth
- Castor set for maximum mobility

VARi IT 501

VARIABLE USE

Thanks to the stable and welded frame construction, the VARi IT can be used in industrial and network environments.

VARIABLE DEPTH

Depending on the housing combination, depths of 400 mm, 700 mm, 850 mm to 1000 mm are possible.

VARIABLE LOCATION

Can be used as a wall-mounted or floor-standing enclosure. Even variable in location thanks to castors

VARIABLE ACCESS

Optimum accessibility and quick access thanks to removable cladding parts

VARIABLE CONFIGURATION

Wide range of configuration options and choice of accessories

VARIABLE PROTECTION CLASS

Up to IP 54 possible depending on configuration!

CABLE ENTRY

Top and bottom available with brush or multifunctional plate

PRE-ASSEMBLY

Complete pre-assembly including accessories in the factory

WALL DISTRIBUTOR

(Fig. shows side wall mounting)

STAND DISTRIBUTOR

THE ADVANTAGES OF
VARi IT 501

apra 19" FLOOR-STANDING/ WALL-DISTRIBUTION SYSTEM VARI IT

- ✔ Swivel lever with profile half cylinder or electronic access control possible
- ✔ Protection class up to IP 54
- ✔ Variable enclosure depth up to D = 1000 mm
- ✔ EMC-protected variant available
- ✔ Housing including accessories com pletely pre-assembled (ready for immediate use)
- ✔ Targeted advice tailored to your needs on site or from our internal sales team
- ✔ System can be extended with an active air conditioning unit
- ✔ Modern two-tone design

Other 19" FLOOR/ WALL-DISTRIBUTION SYSTEMS

- X 08/15 locking (without protection!)
- X Low degree of protection - often only IP 20
- X Only one housing depth available
- X No EMC version available
- X Delivered in individual parts (self-assembly of components required)
- X Own research via internet plat forms/ No qualified advice
- X Passive ventilation/single fan
- X 08/15 Optics

www.apra.de